WO 2005/058188 PCT/IB2004/052741

7

## CLAIMS:

1. A system for resonantly driving a power toothbrush having a resonant frequency, wherein a brushhead portion of the toothbrush moves in operation through a path with an amplitude about a center point, comprising:

a resonant drive system for driving a brushhead at a drive frequency, the drive system including a circuit for changing the drive frequency relative to the center frequency to produce a periodic change of amplitude of the brushhead portion within the range of 5-30%, providing an improved sensory experience without discomfort to the user.

- 2. The system of claim 1, wherein the change of amplitude is less than 20%.
- 3. The system of claim 1, wherein the center frequency is different from the resonant frequency of the toothbrush within a range of 0 to 5 Hz.
- 4. The system of claim 3, wherein the changing of the drive frequency is accomplished by frequency modulation.
- 5. The system of claim 4, wherein the difference between the center frequency and the resonant frequency is approximately  $\pm 3$  Hz.
- 6. A system of claim 1, wherein the driving frequency has a frequency deviation with a range of 1-14 Hz from the center frequency.
- 7. The system of claim 6, wherein the frequency deviation is approximately 3.5 Hz.
- 8. The system of claim 1, wherein the driving frequency change has a modulation frequency within the range of 3-40 Hz.
- 9. The system of claim 8, wherein the modulation frequency is approximately 12 Hz.
- 10. The system of claim 4, wherein the change of the drive frequency is in the form of a triangular wave.
- 11. The system of claim 1, wherein the change of drive frequency has a duty factor of approximately 48%.
- 12. The system of claim 1, wherein the drive system includes two driving signal sources, one signal source being at approximately the resonant frequency and the other signal source being at a frequency which is slightly different than the resonant frequency.
- 13. The system of claim 12, wherein the frequency of the second signal source is different than the frequency of the first source within a range of 5 to 30 Hz.